

## XTP SYSTEMS

### XTP T HWP 101

#### XTP Transmitter for HDMI - Decora® Wallplate

The Extron XTP T HWP 101 is a single-gang Decora®-style transmitter for sending HDMI with embedded audio up to 330 feet (100 meters) over a single shielded CATx cable. The one-gang form factor provides maximum space efficiency for convenient installation in wall mount, floor box, and furniture mount applications. The transmitter is HDCP compliant and supports computer video up to 1920x1200, including 1080p/60 Deep Color and 2K resolutions. It offers many of the integrator-friendly features that are standard with XTP® products, such as EDID Minder® and remote power capability. The single-gang XTP T HWP 101 works with XTP Systems® for signal distribution and long-distance transmission in wall-mount environments.

#### FEATURES

- Transmits HDMI with embedded audio up to 330 feet (100 m) over a shielded CATx cable
- Supports computer video up to 1920x1200, including HDTV 1080p/60 Deep Color and 2K
- Extron XTP DTP 24 shielded twisted pair cable is strongly recommended for optimal performance
- EDID Minder® automatically manages EDID communication between connected devices
- Key Minder® continuously verifies HDCP compliance for quick, reliable switching
- Remote power capability
- Compatible with all XTP integrated system products



**NOW SHIPPING**

Model	Version Description	Part Number
XTP T HWP 101	HDMI Decora Transmitter - Black .....	60-1407-12
XTP T HWP 101	HDMI Decora Transmitter - White .....	60-1407-13

### XTP T UWP 202

#### Two Input XTP Transmitter - Decora® Wallplate

The XTP T UWP 202 and XTP T UWP 202 NL are two-input transmitters for sending HDMI or RGBHV video, audio, and bidirectional RS-232 and IR up to 330 feet (100 m) over a shielded CATx cable. The XTP T UWP 202 includes an RJ45 Output port on the front plate to enable Ethernet extension for LAN access. Incoming analog video signals are digitized for reliable display on a variety of output devices. The XTP® transmitters are HDCP compliant and support computer video to 1920x1200, including 1080p/60 Deep Color and 2K signals. These transmitters work with XTP Systems® for signal distribution and long-distance transmission in wall-mount environments.

#### FEATURES

- Transmits HDMI or digitized analog video, audio, and bidirectional RS-232 and IR up to 330 feet (100 m) over a shielded CATx cable
- HDMI and VGA inputs
- Supports computer video up to 1920x1200, including HDTV 1080p/60 Deep Color and 2K
- Extron XTP DTP 24 shielded twisted pair cable is strongly recommended for optimal performance
- Auto-switching between inputs
- Bidirectional RS-232 and IR insertion for AV device control
- EDID Minder® automatically manages EDID communication between connected devices
- Key Minder® continuously verifies HDCP compliance for quick, reliable switching
- Ethernet extension - XTP T UWP 202
- RJ45 for Remote power capability
- RS-232 control
- Selectable analog stereo audio input embedding
- Compatible with all XTP integrated system products
- Mounts in an included two-gang Decora®-style wallplate



XTP T UWP 202



XTP T UWP 202 NL

**NOW SHIPPING**

Model	Version Description	Part Number
XTP T UWP 202	2 Input Decora Transmitter Black .....	60-1216-12
XTP T UWP 202	2 Input Decora Transmitter White .....	60-1216-13
XTP T UWP 202 NL	2 Input Decora Transmitter No LAN Black .....	60-1410-12
XTP T UWP 202 NL	2 Input Decora Transmitter No LAN White .....	60-1410-13

For updated product availability, go to [www.extron.com](http://www.extron.com)

Europe  
+31.33.453.4040 / +800.3987.6673  
+31.33.453.4050 FAX

Middle East  
+971.4.299.1800  
+971.4.299.1880 FAX

Asia  
+65.6383.4400 / +800.7339.8766  
+65.6383.4664 FAX

China  
+86.21.3760.1568 / +4000.398766  
+86.21.3760.1566 FAX

Japan  
+81.3.3511.7655  
+81.3.3511.7656 FAX

**Extron**