

HANDI® 300
SINGLE FACE

| ITEM CODE | | | | | | | |
|---|-------------------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|
| H740/3 | | <input type="checkbox"/> |
| VERSION | | ↑ | ↑ | ↑ | ↑ | ↑ | ↑ |
| Minute 24V/6mA slave movement (without second sweep hand) | <input type="checkbox"/> | 3 | | | | | |
| AFNOR NFS 87500 (230 VAC power supply) | <input checked="" type="checkbox"/> | 9 | | | | | |
| AFNOR NFS 87500 (12-24 VDC power supply) | <input checked="" type="checkbox"/> | 7 | | | | | |
| (¹)ASCII RS 485* (230VAC power supply) | <input checked="" type="checkbox"/> | Q | | | | | |
| NTP Ethernet 10/100BaseT Synchronization (110-240VAC power supply) | <input checked="" type="checkbox"/> | N | | | | | |
| NTP Ethernet 10/100BaseT Synchronization (Power Over Ethernet) | <input checked="" type="checkbox"/> | P | | | | | |
| NTP Wi-Fi Synchronization (IEEE 802.11 a/b/g/n standards 2.4 Ghz) (110-240VAC power supply) | <input checked="" type="checkbox"/> | W | | | | | |
| Synchronisation DCF 24VDC (Code DCF + Power supply (depending on versions) 24V in pair telecom cable) | <input checked="" type="checkbox"/> | B | | | | | |
| MOUNTING | | | | | | | |
| Wall (bracket included) | <input type="checkbox"/> | M | | | | | |
| Anodized grey - Ceiling bracket or flag mounting bracket | <input type="checkbox"/> | P | | | | | |
| Specificity (on request) | | X | | | | | |
| COLOUR CASING | | | | | | | |
| Anodized grey aluminium | <input type="checkbox"/> | 7 | | | | | |
| (²)specific RAL colour (on request) | | X | | | | | |
| Dial design | | | | | | | |
| White dial, arabic figures 1 to 12, small indexes | <input type="checkbox"/> | 0 | | | | | |
| (³)Dial following design in data sheet | <input checked="" type="checkbox"/> | | | | | | |
| (³)Specific dial (on request) | | X | | | | | |
| SWEEP SECONDS HAND OPTION | | | | | | | |
| Without sweep seconds hand | | 0 | | | | | |
| (⁴)Black sweep seconds hand | <input type="checkbox"/> | N | | | | | |
| (⁴)Red sweep seconds hand | <input type="checkbox"/> | G | | | | | |
| OPTION | | | | | | | |
| (⁵)Synchronization loss Led alarm AFNOR in front face | <input type="checkbox"/> | A | | | | | |

(1) 9600 bauds 8 bits without parity

(2) Quantity min. 10 units

(3) Quantity min. 5 units

(4) Sweep seconds hand not available in pulse version

(5) Only for AFNOR NFS 87500 versions (version 7 or 9)